

12" x 12"
seat sizes now
available with
iLevel®
-SOF ONLY-

NOW AVAILABLE
WITH ACCU-TRAC
ADVANCED TRACKING
TECHNOLOGY
AND
8" SOLID CASTERS





With features like standard 6 mph motors and advanced responsiveness,

the Q6 Edge® 2.0 is engineered to meet the performance needs of the most active user. The Q6 Edge 2.0 accepts a complete range of seating and electronics options to deliver exceptional rehab capability at an excellent value, and is available with our iLevel® technology.

e Reliablo Lough

Authoritation of the second

(US) 866-800-2002

(CAN) 888-570-1113

Specifications

DRIVE WHEELS	Standard: 14" Solid Optional: 14" Pneumatic
CASTER WHEELS	Front: 6" Solid (Optional: 8" Solid) Rear: 6" Solid (Optional: 8" Solid)
ANTI-TIP WHEELS	N/A
MAXIMUM SPEED ¹	Up to 6 mph
GROUND CLEARANCE	2.7" (battery tray)
TURNING RADIUS ²	20.5" with 6" casters 23.25" with 8" casters
OVERALL LENGTH ²	35.5" with 6" casters 40.48" with 8" casters
BASE WIDTH	24.4"
SEATING SIZES	
Synergy®/TRU-Balance® 3 Static Seat	Width: 10-22" Depth: 10-22"
TRU-Balance® 3 Power Tilt	Width: 12-22" Depth: 12-22"
TRU-Balance® 3 Lift & Tilt	Width: 16-22" Depth: 14-22"
SEAT-TO-FLOOR HEIGHTS	
Synergy®/TRU-Balance® 3 Static Seat ⁵	16.5-18.5"
TRU-Balance® 3 Power Tilt ⁵	17.5-19.5"
TRU-Balance® 3 Lift & Tilt ⁵	17.5-19.5"
MANUAL TILT/RECLINE ⁶	Yes
BATTERY SIZE ³	NF-22
BATTERY WEIGHT ⁷	38 lbs.
AVAILABLE ELECTRONICS 8	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 100A Q-Logic 2 EX
BATTERY CHARGER	8A Off-board
MOTOR PACKAGES	2-Pole Mid-Wheel 6®
WEIGHT CAPACITY ⁴	300 lbs.
BASE WEIGHT	138.6 lbs. with 6" casters 148 lbs. with 8" casters
MEDICARE CODE COVERAGE	Group 3: Standard (K0848/K0849), Single Power (K0856), Multiple Power (K0861)

- 1) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.
- 2) Without front riggings
- 3) Battery capacity may change when adding power positioning systems.
- Weight capacity is dictated by the selection of seating.
- 3/8" with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details.

 Listed measurements are in the lowest position; does not include elevating system unless specified.
- 6) The Synergy® Manual Tilt weight capacity is 75 lbs. and maximum dimensions are 14" W x 14" D. Maximum dimensions of the Manual Recline vary by power base and seating system. Call for details.
- 7) Battery weight may vary +/- 3 lbs. based on manufacturer.
- 8) All Quantum Rehab® units can be ordered with specialty controls.
- 9) Call for availability

Features

- Standard 6 mph motors offer advanced performance, precise control and responsiveness via innovative singlestage gearbox
- Bold aesthetics
- iLevel® option available with up to 10" of seat elevation (in 16 seconds) at walking speed (up to 3.5 mph)
- iLevel is retrofittable on the Q6 Edge® 2.0

Options

- iLevel® option allows 10" of seat elevation in 16 seconds while at walking speed (3.5 mph)
- TRU-Balance® 3 Seating
- TRU-Comfort 2 Seating
- Q-Logic 2 EX Drive Controls
- Trilogy vent tray⁹
- Compact vent tray⁹

- LED full lighting package
- 4" wide flat-free knobby extended traction tires⁹
- New LED fender lights
- 12" x 12" seat sizes with iLevel (SOF only)
- 8" solid casters
- Accu-Trac Advanced Tracking Technology





New LED fender lights

New 8" casters

Colors

SEAT BACKS for units without TRU-Balance® 3 are only available in *Back in Black*.





(US) 866-800-2002 • (CAN) 888-570-1113 • www.quantumrehab.com • www.ilevel.rehab











