

# Victory® 10 (4-wheel)

# ENHANCE YOUR ACTIVE LIFESTYLE WITH ADDED COMFORT AND PERFORMANCE

The Victory® 10 series offers added style, comfort and performance for your active lifestyle. Standard features include LED lighting package, backlit battery gauge, feather touch disassembly, wraparound delta tiller, 10" solid tires and a front basket. A 400 lb. weight capacity, a per charge range of up to 15.5 miles and a maximum speed up to 5.25 mph compliment the versatility of the Victory 10. Available in Viper Blue and Candy Apple Red.



Victory® 10 (3-wheel) Shown with optional 22" wide high-back seat







# **SPECIFICATIONS**

### VICTORY® 10 3-Wheel (3W): SC610 4-Wheel (4W): SC710

Weight capacity:	400 lbs.
Maximum speed1:	Up to 5.25 mph
Ground clearance <sup>3</sup> :	3" at mid-frame
Turning radius <sup>3</sup> :	3W: 42" 4W: 54"
Overall length <sup>3</sup> :	3W: 45.25" 4W: 47"
Overall width <sup>3</sup> :	22.25"
Seat-to-deck height <sup>3</sup> :	17.5"-19"
Seat-to-ground height range:	20.5"-22"
Front tires:	3.5" x 10" solid
Rear tires:	3.5" x 10" solid
Range per charge <sup>1,2</sup> :	Up to 15.5 miles
Total weight without batteries <sup>1,3</sup> :	3W: 133.5 lbs. 4W: 137.5 lbs.
Heaviest piece when disassembled <sup>3,6</sup> :	3W: 54.5 lbs. (front section) 4W: 61 lbs. (front section)
Standard seating:	Type: Foldable molded plastic Weight: 28 lbs. Material: Black Vinyl Dimensions: 18" width, 17" depth
Drive system:	Rear-wheel drive, sealed transaxle with 24-volt DC motor
Dual braking system:	Electronic, regenerative and electromechanical
Battery requirements <sup>4,5</sup> :	(2) 12V deep-cycle (standard) Size: U-1 or 40 AH (optional) Weight: (U-1) 24.5 lbs. each, (40 AH) 32.5 lbs. each
Battery charger:	3-amp, off-board (U-1), 5-amp, off-board (40 AH)

Color:



Candy Apple Red



Viper Blue

# **Pride Lifts & Ramps**

Compatible Lifts:

Backpacker® Plus
 Outlander

# **FEATURES**

- Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- Delta tiller with wraparound handles
- Backlit battery gauge
- Exclusive stylish, lightweight, non-scuffing, black, low-profile tires
- Long-lasting, high-intensity LED headlight offers optimal pathway illumination
- Lightweight pinchless hinge seat eight position rotation, sliders and viscoelastic foam inserts for increased comfort
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port
- · Auto-connecting front-to-rear harness

## **OPTIONS**

- Forearm crutch holder
- · Cane/crutch holder
- · Oxygen tank holder
- · Cup holder
- · Rear basket
- Safety flag
- Walker holder
- Weather cover
- Saddlebag
- Cell phone holder
- Touch-up paint
- 18"W x 18"D black vinyl reclining high-back seat, with sliders, height adjustable headrest, flip-up, height and width adjustable armrest
- 22"W x 18"D black vinyl reclining high-back seat height adjustable headrest, flip-up, height and width adjustable armrest
- · Additional optional seat sizes available
- 40 AH batteries

Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
 Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results

2 lesses in accordance with Avactives, less voice, ecclosers at 100 horses standards. Residence derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

3 Due to manufacturing tolerances and continual product improvement, this specification can

be subject to a variance of (+ or -) 3%

4 AGM or gel cell type required.
5 Battery weight may vary based on battery manufacturer.

6 Includes standard seat weight.

### NOTE: All specifications subject to change without notice

tained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or – 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections



